



#### USB SMART CARD READER

- **Easy to install** - Eliminates the need to install drivers; uses native supported CCID drivers within the operating system.
- **Readily Compliant** - Meets all relevant industry standards for smooth integration in PC environment
- **Convenient and Reliable** - Multiple-base mounting options, robust housing, long USB cable
- **Suits Any Application** - Compatible with virtually any smart card and major PC operating system

The OMNIKEY® 3121 is a high-performance, USB smart card reader for desktop use that features multiple-base mounting options and a robust housing. Compliant with all industry standards, this reader is compatible with virtually any contact smart card, operating system and a variety of applications. The

OMNIKEY 3121 is easy to install and well-suited for all contact smart card operations, including single sign-on, online banking or digital signature applications.



### FEATURES:

- Meets major standards, including ISO 7816, USB CCID, PC / SC, and HBCI (Home Banking Computer Interface) Specification
- Supports power management to support low energy schemes
- UPC barcode for easier logistics
- Bulk or single packaging option available
- Interchangeable standing base options available for both vertical and horizontal configurations
- USB CCID support makes integration into an existing system the easiest ever
- by connecting host and smart card reader without the need for additional drivers
- All major operating systems supported
- Meets GSA FIPS 201 requirements
- Supports high-speed data transmission



hidglobal.com

North America: +1 512 776 9000  
 Toll Free: 1 800 237 7769  
 Europe, Middle East, Africa: +44 1440 714 850  
 Asia Pacific: +852 3160 9800  
 Latin America: +52 55 5081 1650

© 2018 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and OMNIKEY are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
 2018-02-21-omnikey-3121-usb-desktop-reader-ds-en PLT-00318

An ASSA ABLOY Group brand

ASSA ABLOY

### SPECIFICATIONS

Base Model Number	OMNIKEY® 3121
<b>SMART CARD INTERFACE</b>	
Card Size	ID-1 (Full size)
Standards	ISO 7816
Supported Card Types	Class A: 5V @ 60 mA; Class B: 3 V @ 60 mA; Class C: 1.8V @35 mA ATR response time up to 1.6 s
Protocols	Asynchronous: T=0; T=1 Synchronous: S=8 (I <sup>2</sup> C) ; S=9 (3-wire); S=10 (2-wire)
Insertion Cycles	100,000
Smart Card Interface Speed	420 kbps
Smart Card Clock Frequency	up to 12 MHz
Smart Card detection	Movement detection with auto power-off; Automatic detection of smart card type; Short circuit and thermal protection
8-Pin Handling	C4 / C8 supported
<b>HOST INTERFACE</b>	
USB Interface	USB 2.0 Full Speed Device (12 MBps) USB 3.0 extended operability, tested with hubs/controllers
Connector / Cable	USB Type A connector; 59.1" (150 cm) cable
Operating Systems	Windows 10/8.1/8/7/Vista/Server 2012/Server 2008R2 Windows CE (5/6/7) depending on hardware Linux Debian 6.0+ / Ubuntu 11.04+/ Fedora 15+; Open SUSE 11.4+ Mac OS X; AndroidTM
Driver	CCID native driver from operating system
Supported APIs	PC/SC - API
<b>HUMAN INTERFACE</b>	
Status indicator	Dual-color LED (green & red)
<b>HOUSING</b>	
Housing	Two-tone grey, ABS plastics
Dimensions	3.15" x 2.64" x 1.1" (80 x 67 x 28 mm)
Weight	Reader only 3.88 oz (110g); Standard standing base 1.09 oz (31g)
<b>OPERATING CONDITIONS</b>	
Operating Temperature	32-131 F (0-55°C)
Operating Humidity	10-90% rH
Storage Temperature	-4 - 176 F (-20 - 80°C)
Meantime Between Failure (MTBF)	500,000 hours
<b>COMPLIANCE AND REGULATORY</b>	
Compliance / Certification	EMVCo Terminal Level 1 USB 2.0; TAA; GSA Fips 201 approved list
Regional certifications	CE, FCC, UL, VCCI, KCC, MIC, RCM (C-Tick)
Environmental	WEEE, RoHS, Reach
<b>OPERATING CONDITIONS</b>	
Warranty	Two-year manufacturer's warranty
<b>OPTIONS</b>	
Part Numbers	R31210320-01 (Standard); R31210349-1 (TAA, ROM); R31210399 (TAA, Flash)

### GEP-TECHNOLOGIES

36, Route Nationale Dely Ibrahim  
 Tél.: +213 (0) 23 31 20 47  
 Fax: +213 (0) 23 24 16 72

E-mail: [contact@gep-technologies.dz](mailto:contact@gep-technologies.dz)  
[www.gep-technologies.dz](http://www.gep-technologies.dz)